

Investigating the properties of Al-SiO₂ composite fabricated by the powder metallurgy method

Mohammad Pourabas¹, Mehdi Ghobeiti Hasab^{2,*}, Ali Heidary Moghadam³

¹Department of Mechanical Engineering, Dezful Branch, Islamic Azad University, Dezful, Iran

^{2,3}Department of Metallurgy and Materials, Dezful Branch, Islamic Azad University, Dezful, Iran

Received: January 2016, Revised: February 2016, Accept: April 2016

Abstract

In this research, aluminum-silica composite was fabricated by the powder metallurgy method and using different weight amounts of aluminum and silica powders. After mixing of powders, uniaxial pressing and sintering were applied in pressure of 600 MPa and temperature of 550 °C during 2 hours under argon atmosphere. The pills with diameter of 3 cm and thickness of 5 mm were prepared using 10 g powder. Results showed that with increasing the silica percentage, the density and hardness of composite decreased. With Adding the silica up to %15, the wear resistance of composite increased, however, beyond this amount the wear resistance decreased.

*Corresponding author: ghobeiti@ut.ac.ir

Keywords: Aluminum-Silica composite, Density, Hardness, Wear resistance, Powder metallurgy.

Please cite this article as:

M. Pourabas, M. Ghobeiti-Hasab, A. Heidary-Moghadam, Investigating the properties of Al-SiO₂ composite fabricated by the powder metallurgy method, Journal of Energy Conversion, 2(1) (2016)*-* [In Persian]